

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Please amend the claims as follows:

1. (Currently Amended) A method, comprising:
using credential information stored in a subscriber identity module (SIM)
associated with a General Packet Radio Service (GPRS) adapter to
authenticate access to a [[new]] wireless local area network (WLAN),
wherein an access to a GPRS network via the GPRS adapter is
authenticated using the credential information, and communications
with the SIM and the WLAN are carried out using extensible
authentication protocol for subscriber identity module (EAP-SIM).
2. (Original) The method of claim 1, further comprising:
issuing one or more requests via a smart card interface to get the credential
information.
3. (Original) The method of claim 2, further comprising:
arbitrating the one or more requests to the SIM when the SIM is busy.
4. (Original) The method of claim 3, wherein the one or more requests are
received by the SIM via a SIM reader driver.
5. (Original) The method of claim 4, further comprising:
receiving the credential information from the SIM after the one or more
requests are processed by the SIM.

6. (Original) The method of claim 1, further comprising:
establishing a WLAN connection with the WLAN via a WLAN adapter.
7. (Cancelled)
8. (Previously Presented) The method of claim 6, further comprising:
issuing a location update to switch data services from the GPRS network to
the WLAN; and
disconnecting from the GPRS network.
9. (Currently Amended) A computer-readable medium including machine
readable instructions that, if executed by a computer system, cause the
computer system to perform a method comprising:
using credential information stored in a subscriber identity module (SIM)
associated with a General Packet Radio Service (GPRS) adapter to
authenticate access to a [[new]] wireless local area network (WLAN),
wherein an access to a GPRS network via the GPRS adapter is
authenticated using the credential information, and communications
with the SIM and the WLAN are carried out using extensible
authentication protocol for subscriber identity module (EAP-SIM).
10. (Previously presented) The computer-readable medium of claim 9, further
comprising:
issuing one or more requests via a smart card interface to get the credential
information.
11. (Previously presented) The computer-readable medium of claim 10, further
comprising: arbitrating the one or more requests to the SIM when the SIM is
busy.

12. (Previously presented) The computer-readable medium of claim 11,
wherein the one or more requests are received by the SIM via a SIM reader
driver.
13. (Previously presented) The computer-readable medium of claim 12, further
comprising:
receiving the credential information from the SIM after the one or more
requests are processed by the SIM.
14. (Previously presented) The computer-readable medium of claim 9, further
comprising:
establishing a WLAN connection with the WLAN via a WLAN adapter.
15. (Cancelled)
16. (Previously Presented) The computer-readable medium of claim 14, further
comprising:
issuing a location update to switch data services from the GPRS network to
the WLAN; and
disconnecting from the GPRS network.
17. (Currently Amended) A system, comprising:
a wireless local area network (WLAN) adapter;
a general packet radio service (GPRS) adapter coupled to the WLAN adapter
and including a subscriber identity module (SIM); and
a mobility client to initiate requests for credential information from the SIM
to authenticate access to a [[new]] WLAN when the mobility recognizes
an access point, wherein an access to a GPRS network via the GPRS
adapter is authenticated using the credential information, and said
requests for the credential information are communicated to the SIM

using extensible authentication protocol for subscriber identity module (EAP-SIM).

18. (Original) The system of claim 17, wherein the requests for the credential information are communicated to the SIM via a smart card interface.
19. (Original) The system of claim 18, wherein the requests for the credential information are received by the SIM via a SIM reader driver.
20. (Original) The system of claim 19, wherein the GPRS adapter includes a SIM access module (SAM) to arbitrate the request for the credential information to the SIM.
21. (Cancelled)
22. (Previously Presented) The system of claim 20, wherein the mobility client is further to issue a location update after the access to the WLAN is authenticated and a WLAN connection is established.
23. (Previously Presented) The system of claim 22, wherein the mobility client is further to disconnect from the GPRS network.
24. (Cancelled)
25. (Original) The system of claim 17, wherein the WLAN adapter and the GPRS adapter are installed on an open platform.
26. (Original) The system of claim 17, wherein the WLAN adapter and the GPRS adapter are combined into one module.
27. (Currently Amended) A system, comprising:

means for initiating requests for credential information from a subscriber identity module (SIM) associated with a general packet radio service (GPRS) adapter, wherein a GPRS connection via the GPRS adapter is authenticated using the credential information;

means for utilizing the credential information to authenticate access to a [[new]] wireless local area network (WLAN) using extensible authentication protocol for subscriber identity module (EAP-SIM); and

means for switching data services from the GPRS connection to a WLAN connection after the access to the WLAN is authenticated.

28. (Original) The system of claim 27, wherein said means for requesting the credential information from the SIM includes means for arbitrating requests to the SIM.

29. (Original) The system of claim 28, wherein said means for switching data services between the GPRS connection and the WLAN connection includes means for performing a location update.

30. (Original) The system of claim 27, further comprising:
means for interfacing with the SIM to send the request for the credential information.

31. (Currently Amended) A method, comprising:
issuing one or more requests to a Subscriber Identity Module (SIM)
associated with a General Packet Radio Service (GPRS) adapter using
Extensible Authentication Protocol (EAP), wherein a GPRS connection via
the GPRS adapter is authenticated using credential information stored in
the SIM;
arbitrating the one or more requests to the SIM when the SIM is busy;
receiving the credential information stored in the SIM via a SIM reader
driver;

utilizing the credential information to authenticate access to a [[new]]
Wireless Local Area Network (WLAN) using extensible authentication
protocol for subscriber identity module (EAP-SIM);
establishing a WLAN connection with the WLAN via a WLAN adapter;
issuing a location update to switch data services from the GPRS connection
to the WLAN connection; and
disconnecting from the GPRS connection.

32. (Currently Amended) A computer-readable medium including machine
readable instructions that, if executed by a computer system, cause the
computer system to perform a method comprising:
- issuing one or more requests to a Subscriber Identity Module (SIM)
associated with a General Packet Radio Service (GPRS) adapter using
Extensible Authentication Protocol (EAP)), wherein a GPRS connection
via the GPRS adapter is authenticated using credential information stored
in the SIM;
- arbitrating the one or more requests to the SIM when the SIM is busy;
- receiving the credential information stored in the SIM via a SIM reader
driver;
- utilizing the credential information to authenticate access to a [[new]]
Wireless Local Area Network (WLAN) using ~~EAP~~ extensible authentication
protocol for subscriber identity module (EAP-SIM);
establishing a WLAN connection with the WLAN via a WLAN adapter;
issuing a location update to switch data services from the GPRS connection
to the WLAN connection; and
disconnecting from the GPRS connection.